

## Parallel Connectors DU-AL Cable - Cable







The "DU" parallel connector is used for making strandedcable splices. It is designed to withstand high pullout forces and provide a positive mechanical joint over a long period of service.

CABLE RANGE				CATALOG	FIGURE	DIMENSIONS	U-BOLT
RUN		TAP		NUMBER	NUMBER	IN INCHES	DAIMETER
ALUMINUM	A.C.S.R.	ALUMINUM	A.C.S.R.	NUMBER	NUNDER	L	TAP
6 to 2/0	6 to 1/0	6 to 2/0	6 to 1/0	DU-100-AL	1	2 1/2	1/2
1/0 to 300	1/0 to 266.8	6 to 2/0	6 to 1/0	DU-221-AL	1	3 1/2	1/2
1/0 to 300	1/0 to 266.8	1/0 to 300	1/0 to 266.8	DU-120-AL	1	3 1/2	1/2
300 to 500	266.8 to 397.5	6 to 2/0	6 to 1/0	DU-229-AL	1	3 3/4	1/2
300 to 500	266.8 to 397.5	1/0 to 300	1/0 to 266.8	DU-232-AL	1	3 3/4	1/2
300 to 500	266.8 to 397.5	300 to 500	266.8 to 397.5	DU-130-AL	1	3 3/4	1/2
500 to 800	397.5 to 666.6	1/0 to 300	1/0 to 266.8	DU-240-AL	1	4 3/4	5/8
500 to 800	397.5 to 666.6	300 to 500	266.8 to 397.5	DU-241-AL	1	4 3/4	5/8
500 to 800	397.5 to 666.6	500 to 800	397.5 to 666.6	DU-140-AL	1	4 3/4	5/8
750 to 1000	636 to 900	1/0 to 300	1/0 to 266.8	DU-249-AL	2	5 3/8	5/8
750 to 1000	636 to 900	300 to 500	266.8 to 397.5	DU-250-AL	2	5 3/8	5/8
750 to 1000	636 to 900	500 to 800	397.5 to 666.6	DU-251-AL	2	5 3/8	5/8
750 to 1000	636 to 900	750 to 1000	636 to 874.5	DU-150-AL	2	5 3/8	5/8
1000 to 1500	900 to 1272	500 to 800	397.5 to 666.6	DU-260-AL	2	5 3/4	5/8
1000 to 1500	900 to 1272	750 to 1000	636 to 874.5	DU-261-AL	2	5 3/4	5/8
1000 to 1500	900 to 1272	1000 to 1500	874.5 to 1272	DU-160-AL	2	5 3/4	5/8



